

# THROUGH WALL SYSTEMS Sheet 1 of 2

Product: thruWall Depositories

Catalog #: 19-0003 driveDrop Thick Wall Extension Kit

Date: January 1, 2018. Go to <a href="https://www.kingsley.com">www.kingsley.com</a> for all updates. Specifications are subject to change without notice. MADE IN THE USA

#### **INCLUDED WITH THIS SYSTEM:**

The 4Ever Thick Wall Extension kit comes with an extension chute that telescopes over the standard chute of the Through Wall unit itself. This longer chute allows the unit to be used in walls up to 24 inches thick. The extension kit also comes with a longer aluminum slide to accommodate the added length.

### TRANSPORT CARTS USED WITH THIS SYSTEM:

Contingent on height of installation, can be used with any Kingsley receiving cart. Also compatible with most conveyer systems.

**COMPATIBLE THROUGH WALL DEPOSITORIES USED WITH THIS SYSTEM:** 10-8175

ACCESSORIES/OPTIONS FOR THIS SYSTEM:

N/A

## THROUGH WALL INTERIOR CONSTRUCTION/FEATURES

**Construction** All aluminum construction. All edges are honed smooth.

Materials:

The chute housing has four sides. The slide chute is

**Construction** equipped with interlocking system.

Methods:

The angle of the entry chute, length of the slide chute

and the Airbloc system prevent reaching inside through the depository door and block attempts to phish materials

**Deterrence:** with a claw apparatus.

Locking

Theft

Method: N/A

ADA

**Compliancy:** ADA compliant when properly installed.

Assembly

**Required:** Attach slide to system.

# 19-0003 drive Drop Thick Wall Extension Kit Continued

#### Overall Dimensions:

**Shell Dimensions:** 20-1/8"L x 14-5/8" W x 18-1/4"H [511.18mmL x 371.48mmW x

463.55mmH]

**Slide Dimensions:** 22-1/2"L x 17-11/16" W x 1/16"H [571.5mmL x 449.26mmW x

1.59mmH]

Product

Weight:

9 lbs [4.08kg]

Shipping

Method/Class:

Ground or LTL/Class 150

**INSTALLATION** (Rough cut only. Please visit <a href="www.kingsley.com">www.kingsley.com</a> for complete instructions)

Rough Cut dimensions and trim 36-1/2" [927.10mm] from exterior floor to bottom of

cut out.

Rough cut opening 20¼W x 18-5/16"H [514.4mmW x

465.1mmH] all the way through wall.

1/4" [6.35mm] trim on the top, bottom and sides of

opening.